

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 02-Jul-2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: ORANGE TOUGH 15

Product Number: 2215 , 2216
Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 1
Skin Sensitization: Category 1

GHS Label Elements

Signal Word: Danger

Symbols:

I LE

Hazard Statements: Causes skin irritation

Causes serious eye damage May cause an allergic skin reaction

Precautionary Statements:

Prevention: Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Response:

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN.

-Skin IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash

before reuse If skin irritation or rash occurs: Get medical attention.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Revision Date: 02-Jul-2021 2215 - ORANGE TOUGH 15

Not Applicable Storage:

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: · Harmful if swallowed

• Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	40-70
Dipropylene Glycol Butyl Ether	29911-28-2	5-10
Triethanolamine	102-71-6	1-5
Alkylbenzene Sulfonic Acid	68584-22-5	1-5
Soy Methyl Esters	67784-80-9	1-5
Limonene	5989-27-5	1-5
Undeceth-3	34398-01-1	1-5
Sodium Xylenesulfonate	1300-72-7	0.1-1
Tetrasodium EDTA	64-02-8	0.1-1
Colorant	PROPRIETARY	<0.1
Colorant	PROPRIETARY	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash with plenty of soap and water. Take off contaminated clothing and wash before

reuse. If skin irritation or rash occurs: Get medical attention.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a -Inhalation:

poison control center or physician if you feel unwell.

-Ingestion: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention if you feel unwell.

Treat symptomatically. Note to Physicians:

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the Chemical:

Dried product is capable of burning. Combustion products are toxic.

-Skin Contact:

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray. **Precautions for Firefighters:**

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for Clean-Up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

2215 - **ORANGE TOUGH 15** Revision Date: 02-Jul-2021

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach **Storage Conditions:**

of children. Keep from freezing.

Suggested Shelf Life: Minimum of 2 years from date of manufacture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Triethanolamine	TWA: 5mg/m ³	-	-
102-71-6	_		

Engineering Controls: Provide good general ventilation.

> If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Wear rubber or other chemical-resistant gloves. Skin and Body Protection:

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Orange
Odor:	Orange
pH:	8.5-9.0
Melting Point / Freezing Point:	No information available
Boiling Point / Boiling Range:	100 °C / 212 °F
Flash Point:	99 °C / 210 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available
Upper Flammability Limit:	No information available
Lower Flammability Limit:	No information available
Vapor Pressure:	No information available
Vapor Density:	No information available
Specific Gravity:	1.00
Solubility(ies):	Miscible in water
Partition Coefficient:	No information available
Autoignition Temperature:	No information available
Decomposition Temperature:	No information available
Viscosity:	No information available

10. STABILITY AND REACTIVITY

2215 - ORANGE TOUGH 15 Revision Date: 02-Jul-2021

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition May include carbon monoxide, carbon dioxide

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact: Pain, redness and cracking of the skin.
 -Inhalation: Nasal discomfort and coughing.
 -Ingestion: Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Chronic Toxicity: Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 5322 mg/kg ATEmix (dermal): 5322 mg/kg

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available	
Dipropylene Glycol Butyl Ether 29911-28-2	= 1620 µL/kg (Rat)	Not Available	= 42.1 ppm (Rat) 4 h	
Triethanolamine 102-71-6	= 4190 mg/kg (Rat)	> 20 mL/kg (Rabbit)	Not Available	
Alkylbenzene Sulfonic Acid 68584-22-5	= 775 mg/kg (Rat)	= 2000 mg/kg (Rabbit)	Not Available	
Limonene 5989-27-5	= 5200 mg/kg (Rat) = 4400 mg/kg (Rat)	> 5 g/kg(Rabbit)	Not Available	
Sodium Xylenesulfonate 1300-72-7	= 1000 mg/kg (Rat)	Not Available	Not Available	
Tetrasodium EDTA 64-02-8	= 1658 mg/kg(Rat)	Not Available	Not Available	

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Dipropylene Glycol Butyl Ether 29911-28-2	Not Available	841: 96 h Poecilia reticulata mg/L LC50 static	Not Available	Not Available
Triethanolamine 102-71-6	216: 72 h Desmodesmus subspicatus mg/L EC50 169: 96 h Desmodesmus subspicatus mg/L EC50	10600 - 13000: 96 h Pimephales promelas mg/L LC50 flow-through 1000: 96 h Pimephales promelas mg/L LC50 static 450 - 1000:	Not Available	Not Available

2215 - ORANGE TOUGH 15 Revision Date: 02-Jul-2021

		96 h Lepomis macrochirus mg/L LC50 static		
Alkylbenzene Sulfonic Acid 68584-22-5	Not Available	3: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	2.9: 48 h Daphnia magna mg/L EC50
Limonene 5989-27-5	Not Available	0.619 - 0.796: 96 h Pimephales promelas mg/L LC50 flow-through 35: 96 h Oncorhynchus mykiss mg/L LC50	Not Available	Not Available
Tetrasodium EDTA 64-02-8	1.01: 72 h Desmodesmus subspicatus mg/L EC50	41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static	Not Available	Not Available

Persistence and Degradability:

Bioaccumulation:

No information available.

No information available.

Marine Pollutant: Yes.

Other Adverse Effects: No information available

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:Dispose of in accordance with federal, state and local regulations.
Contaminated Packaging:
Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT: Not Regulated

Proper Shipping Name: Non Hazardous Product

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size,

and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN3082

Proper Shipping Name: Environmentally hazardous product, liquid, n.o.s., (contains d-limonene), Marine Pollutant

Hazard Class: 9
Packing Group: III
Marine Pollutant: Yes.

Additional information: According to IMDG Code 2.10.2.7, marine pollutants packed in single or inner packagings

with a capacity of not more than 5 L or 5 kg are excluded from marine pollutant marking

requirements.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:
Chronic Health Hazard:
No
Fire Hazard:
Sudden release of pressure hazard:
No
Reactive Hazard:
No

California Proposition 65

2215 - ORANGE TOUGH 15 Revision Date: 02-Jul-2021

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 1 Instability: 0 Special: N/A

HMIS Health Hazards: 3 Flammability: 1 Physical Hazards: 0

Revision Date: 02-Jul-2021 Reasons for Revision: Section, 14

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet