

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 18-May-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: SHINELINE BASEBOARD STRIPPER

Product Number: 6097

Recommended Use: Stripping solution

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity - Inhalation (Vapors)
Skin Corrosion/Irritation:
Category 4
Category 1
Serious Eye Damage/Eye Irritation:
Category 1
Liquefied gas
Flammable Aerosols
Category 1
Category 1

GHS Label Elements

Signal Word: Danger Symbols:



Hazard Statements: Harmful if inhaled.

Causes severe skin burns and serious eye damage. Contains gas under pressure; may explode if heated

Extremely flammable aerosol.

Precautionary Statements:

Prevention: Use only outdoors or in a well-ventilated area.

Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing. Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Response: IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for -Inhalation:

breathing.

-Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information. -Specific Treatment:

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122°F Storage:

(50°C) Store in a well-ventilated place

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: · Corrosive.

· Harmful if swallowed

· Harmful contact may not cause immediate pain.

· Harmful if absorbed through skin.

• Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|-----------------|-----------|----------|
| water | 7732-18-5 | 60-100 |
| 2-butoxyethanol | 111-76-2 | 7-13 |
| N-butane | 106-97-8 | 1-5 |
| propane | 74-98-6 | 1-5 |

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and -Eye Contact:

easy to do, Continue rinsing, IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. -Skin Contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. -Inhalation:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR -Ingestion:

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water spray (fog), Foam

Specific Hazards Arising from the

Chemical:

Extremely flammable aerosol. Exposure to high temperature may cause containers to burst.

Bursting aerosol containers may be propelled from fire at high speed.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full **Protective Equipment and**

Precautions for Firefighters: protective gear. Water may be used to cool closed containers to prevent pressure build-up

and possible auto ignition or explosion when exposed to extreme heat.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Environmental Precautions: Methods for Clean-Up:

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Intentional misuse

by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after

handling.

Storage Conditions: NFPA 30B Level 1 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°.

Exposure to high temperature may cause containers to burst. Keep out of the reach of

children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH |
|-----------------------------|---------------|---|--|
| 2-butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³ |
| N-butane 106-97-8 | TWA: 1000 ppm | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | TWA: 800 ppm TWA: 1900 mg/m ³ |
| propane 74-98-6 | TWA: 1000 ppm | TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ | IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ |

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection:

Wear rubber or other chemical-resistant gloves.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

| 9 PHYSICAL | AND CHEMICAL | PROPERTIES |
|------------|--------------|------------|
| | | |

| Appearance/Physical State: | Aerosol | | |
|---------------------------------|---|--|--|
| Color: | Clear | | |
| Odor: | Lemon | | |
| pH: | 11.5-12.0 | | |
| Melting Point / Freezing Point: | No information available. | | |
| Boiling Point / Boiling Range: | 99 °C / 210 °F (Product without propellant) | | |
| Flash Point: | < -18 °C / < 0 °F (Propellant-estimated) | | |
| Evaporation Rate: | < 1 (Butyl acetate = 1) | | |
| Flammability (solid, gas) | No information available. | | |
| Upper Flammability Limit: | No information available. | | |
| Lower Flammability Limit: | No information available. | | |
| Vapor Pressure: | No information available. | | |
| Vapor Density: | No information available. | | |
| Specific Gravity: | 0.980 (Product without propellant) | | |
| Solubility(ies): | No information available. | | |
| Partition Coefficient: | No information available. | | |
| Autoignition Temperature: | No information available. | | |
| Decomposition Temperature: | No information available. | | |
| Viscosity: | No information available. | | |

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition Strong oxidizing agents. Strong a

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact: Pain, redness, blistering and possible chemical burn.

-Inhalation: Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

coughing.

-Ingestion: Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory

System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 3781 mg/kg
ATEmix (dermal): 9649 mg/kg
ATEmix (inhalation-gas): 5891728 mg/l
ATEmix (inhalation-dust/mist): 19.4 mg/l
ATEmix (inhalation-vapor): 19.1 mg/l

Component Acute Toxicity Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------|-----------|-------------|-----------------|
|---------------|-----------|-------------|-----------------|

| water 7732-18-5 | > 90 mL/kg (Rat) | Not Available | Not Available |
|-----------------------------|-------------------|---|--|
| 2-butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 2270 mg/kg (Rat) = 220 mg/kg (Rabbit) | = 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h |
| N-butane 106-97-8 | Not Available | Not Available | = 658 mg/L (Rat)4 h |
| propane 74-98-6 | Not Available | Not Available | = 658 mg/L (Rat)4 h |

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Algae/Aquatic Plants | Fish | Toxicity to | Crustacea |
|-----------------------------|----------------------|---|----------------|---|
| | | | Microorganisms | |
| 2-butoxyethanol 111-76-2 | Not Available | 1490: 96 h Lepomis macrochirus mg/L LC50 | Not Available | 1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 |
| | | static 2950: 96 h Lepomis macrochirus mg/L LC50 | | h Daphnia magna mg/L EC50 |

Persistence and Degradability:
Bioaccumulation:

No information available.
No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with

federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1950
Proper Shipping Name: Aerosols
Hazard Class: 2.1

Special Provisions: This product meets the exception requirements of section 49 CFR 173.306 as a limited

quantity and may be shipped as a limited quantity.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

SARA 311/312 Hazard Categories

Acute Health Hazard:
Chronic Health Hazard:
No
Fire Hazard:
Sudden release of pressure hazard:
Reactive Hazard:
No

California Proposition 65

This product does not contain any Proposition 65 chemicals

16. OTHER INFORMATION

NFPA **Health Hazards: 3** Flammability: 1 Instability: 0 Special: N/A

Health Hazards: 3 Flammability: 2 Physical Hazards: 2 HMIS

Revision Date: 18-May-2015

Reasons for Revision: No information available.

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet