



PERFORMANCE PLUS

BLOWN MACHINE STRETCH FILM

STRETCH FILM DIVISION

BLOWN FILM

TWO-SIDED CLING

EXCELLENT FOR DIFFICULT LOADS

EXCELLENT PUNCTURE

HIGH PERFORMANCE

EXCELLENT LOAD HOLDING CAPABILITY

PERFORMANCE PLUS SERIES

Performance Plus is AEP'S premium blown machine film. Performance Plus has shown tremendous success over the last 15 years. Designed for almost any application, especially for those needing extra toughness and stretchability. Performance Plus is a favorite because of it's ability to compete in any application.



Item Number	Width Inches	Thickness Gauge	Feet/Roll	Weight/Roll	Rolls/Pallet	Standard Stock	Standard Non-Stock
PP-2070	20	70	6,500	36.4	40v	X	
PP-2080-5	20	80	5,000	32.0	40v	X	
PP-2080	20	80	6,000	38.4	40v	X	
PP-2080-BL	20	80	5,000	32.0	32c	X	
PP-3080	30	80	6,000	57.6	20v	X	
PP-2090	20	90	5,000	36.0	40v	X	
PP-20120	20	120	3,750	36.0	40v	X	
UV-20100	20	100	5,500	44.0	32c	X	
PP-2060-SNS	20	60	7,500	36.0	32c		X
PP-5080-SNS	50	80	6,000	96.0	16c		X
PP-6080-SNS	60	80	6,000	115.2	16c		X
PP-20100-SNS	20	100	4,500	36.0	40v		X
PP-30100-SNS	30	100	4,500	54.0	20v		X
PP-30120-SNS	30	120	3,750	54.0	20v		X

Gauge	60	70	80	90	115
Recommended Stretch	230%	250%	275%	280%	290%

<p>Machines and machine settings vary, operating stretch levels may be higher or lower depending on:</p> <ol style="list-style-type: none"> 1. Tension Settings 2. Sharp edges or puncture points 3. Condition of stretch wrapper <ul style="list-style-type: none"> ▪ Soft start ▪ Accel and Decel Rate ▪ Corner Compensation 	<p><u>TYPE OF MACHINERY RECOMMENDED:</u> SEMI-AUTOMATICS AUTOMATICS RINGERS</p>
---	--