

200A

2.0 MIL UTILITY ACRYLIC CST

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Biaxially-oriented polypropylene (BOPP) film coated with pressure-sensitive water based acrylic adhesive.

Best suited for reliable, all-temperature box sealing performance (less than 40°F and greater than 120°F) where resistance to aging, weathering, UV light, and yellowing are important. Provides excellent clarity, high shear strength to prevent 'flagging,' superior quick-stick performance, and controlled unwind to facilitate dispensing on manual or automatic case sealing machines.

PRODUCT APPLICATION

Light to medium weight box sealing and other packaging applications exposed to normal shipping hazards and stress.

NOMINAL VALUES

The following data are nominal values. The data should not be considered as specifications.

Backing	1.1 mil (0.028 mm)
Adhesive	Water Based Acrylic
Elongation (% at break)	100
Adhesion to Steel	> 200 gm/cm
Total Thickness	2.0 mil (0.051 mm)
Color	Clear



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/17

